



Art.Nr. **LNL324/3**



1m	427.9,15381lx	312.64cm
2m	107.0,384.61lx	625.28cm
3m	47.54,170.91lx	937.91cm
4m	26.74,96.161lx	1250.55cm
5m	17.12,61.541lx	1563.19cm
6m	11.89,42.741lx	1875.83cm
7m	8.732,31.401lx	2188.46cm
8m	6.686,24.041lx	2501.10cm
9m	5.283,18.991lx	2813.74cm
10m	4.279,15.381lx	3126.38cm

- 40W
- 5200Lm
- 4000K – neutral white
- IP65
- AC180 - 265V
- 120°
- E
- Recommended ambient temperature -25° to +65°C
- Thermal PC-white
- possibly to connect max. 1000W
- IK08
- Dimension 1200 x 66 x 57 mm
- Weight netto – 828g
- 50000h
- Warranty 5 years
- Non-dimmable
- Packing 1/25

<https://nedes.eu/led-connect.-light-40w/ip65-lw/3/1200/2835/4000k-lnl324/3/p->

[297](#)



Art.Nr. **LNL324/3**



1m	427.9,15381lx	312.64cm
2m	107.0,384.61lx	625.28cm
3m	47.54,170.91lx	937.91cm
4m	26.74,96.161lx	1250.55cm
5m	17.12,61.541lx	1563.19cm
6m	11.89,42.741lx	1875.83cm
7m	8.732,31.401lx	2188.46cm
8m	6.686,24.041lx	2501.10cm
9m	5.283,18.991lx	2813.74cm
10m	4.279,15.381lx	3126.38cm

- 40W
- 5200Lm
- 4000K – neutrálna biela
- IP65
- AC180 - 265V
- 120°
- E
- Doporučená teplota okolia -25° až +65°C
- Thermal PC-biela
- Napájateľné do 1000W
- IK08
- Rozmer 1200 x 66 x 57 mm
- Hmotnosť netto – 828g
- 50000h
- Záruka 5 rokov
- Nestmievateľné
- Balenie 1/25

<https://nedes.sk/led-nadpaj.-svietidlo-40w/ip65-lw/3/1200/2835/4000k-lnl324/3/p297>



Art.Nr. **LNL324/3**



1m	427.9,1538lx	312.64cm
2m	107.0,384.6lx	625.28cm
3m	47.54,170.9lx	937.91cm
4m	26.74,96.16lx	1250.55cm
5m	17.12,61.54lx	1563.19cm
6m	11.89,42.74lx	1875.83cm
7m	8.732,31.40lx	2188.46cm
8m	6.686,24.04lx	2501.10cm
9m	5.283,18.99lx	2813.74cm
10m	4.279,15.38lx	3126.38cm

- 40W
- 5200Lm
- 4000K – neutrální bílá
- IP65
- AC180 - 265V
- 120°
- E
- Doporučená teplota okolí -25° až +65°C
- Thermal PC-bílá
- Napojovatelné do 1000W
- IK08
- Rozměr 1200 x 66 x 57 mm
- Hmotnost netto – 828g
- 50000h
- Záruka 5 let
- Nestmívatelné
- Balení 1/25

<https://nedes.cz/led-prachotesne-svitidlo-40w/ip65-lw/3/1200/2835/4000k-lnl324/3/p-297>



Art.Nr. **LNL324/3**



1m	427.9,15381lx	312.64cm
2m	107.0,384.61lx	625.28cm
3m	47.54,170.91lx	937.91cm
4m	26.74,96.161lx	1250.55cm
5m	17.12,61.541lx	1563.19cm
6m	11.89,42.741lx	1875.83cm
7m	8.732,31.401lx	2188.46cm
8m	6.686,24.041lx	2501.10cm
9m	5.283,18.991lx	2813.74cm
10m	4.279,15.381lx	3126.38cm

- 40W
- 5200Lm
- 4000K – természetes fehér
- IP65
- AC180 - 265V
- 120°
- E
- Ajánlott környezeti hőmérséklet -25° és +65°C
- Thermal PC-fehér
- Sorolható max 1000W
- IK08
- Méret 1200 x 66 x 57 mm
- Nettó tömeg – 828g
- 50000h
- 3 év garancia
- Dimmelhetőség – nem
- Csomagolás 1/25

<https://nedes.hu/led-sorolhato-lampatest-40w/ip65-lw/3/1200/2835/4000k-lnl324/3/p-297>



Art.Nr. **LNL324/3**



1m	427,9,1538lx	312,64cm
2m	107,0,384,6lx	625,28cm
3m	47,54,170,9lx	937,91cm
4m	26,74,96,16lx	1250,55cm
5m	17,12,61,54lx	1563,19cm
6m	11,89,42,74lx	1875,83cm
7m	8,732,31,40lx	2188,46cm
8m	6,686,24,04lx	2501,10cm
9m	5,283,18,99lx	2813,74cm
10m	4,279,15,38lx	3126,38cm

- 40W
- 5200Lm
- 4000K – Neutralweiß
- IP65
- AC180 - 265V
- 120°
- E
- Empfohlene Umgebungstemperatur -25° bis +65°C
- Thermal PC-Weiß
- Verbindung max. 1000W
- IK08
- Dimension 1200 x 66 x 57 mm
- Nettogewicht – 828g
- 50000St
- Garantiezeit 5 Jahre
- Nicht dimmbar
- Verpackung 1/25

<https://nedes.at/led-verbindungsleuchte-40w/ip65-lw/3/1200/2835/4000k-lnl324/3/p-297>

[www.nedes.at](http://www.nedes.at)